

View Online at <https://aerobasegroup.com/nsn/5305-01-485-5025>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

0.302 inches

Fastener Length:

1.375 inches

Head Style:

Flat fillister

Head Diameter:

Between 0.550 inches and 0.562 inches

Head Height:

Between 0.368 inches and 0.375 inches

Internal Drive Style:

Hexagon

End Application:

Eots offload; consolidated automated support system

Thread Diameter:

0.375 inches

Width Across Flats:

Between 0.312 inches and 0.316 inches

Thready Qty Per Inch (tpi):

16

Min. Tensile Strength (psi):

80000 pounds per square inch

Hardness Rating:

80.0 rockwell b

Minimum Yield Strength:

30000 pounds per square inch

Externally Relieved Body Diameter Quantity:

1

Product Name:

Screw, captive

Special Features:

Make from nas1352c6-24

Material:

Stainless steel

Material Specification:

Nas1352c national specification single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unc

Specification Data:

80205-nas1352 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0