## NSN 5305-01-485-5722

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-485-5722 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.425 inches **Fastener Length:** Between 1.660 inches and 1.690 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.265 inches and 0.272 inches **Spline Minor Diameter:** Between 0.1105 inches and 0.1125 inches **Spline Major Diameter:** Between 0.1540 inches and 0.1560 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Internal Drive Style:** Torx **End Application:** F18 e/f **Thread Diameter:** 0.250 inches **Grip Length:** Between 1.240 inches and 1.260 inches Thready Qty Per Inch (tpi): 28 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Criticality Code Justification:** Agav **Product Name:** Bolt, 100 degree reduced head, gear drive recess-ph13-8mo (125 ksi shear), inconel 718 (125 ksi shear), 6al-4v titanium (95 ksi shear) Material: Steel comp xm-13

Unjf

**Passivate** 

**Material Specification:** 

**Thread Series Designator:** 

**Surface Treatment:** 

Ams 5629 assn standard single material response

## NSN 5305-01-485-5722

Close Tolerance Screw - Page 2 of 2



	Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0