NSN 5305-01-486-5436

Machine Screw - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-01-486-5436

| 2 | 2a |
|---|--|
| 7 | Thread Direction: |
| F | Right-hand |
| 7 | Thread Length: |
| C | 0.127 inches |
| F | Fastener Length: |
| E | Between 0.156 inches and 0.187 inches |
| ŀ | lead Style: |
| F | Flat countersunk |
| ŀ | lead Diameter: |
| E | Between 0.238 inches and 0.279 inches |
| l | nternal Drive Style: |
| C | Cross recess type 1 |
| ٦ | Thread Diameter: |
| С | 0.138 inches |
| ٦ | Thready Qty Per Inch (tpi): |
| 3 | 32 |
| 0 | Countersink Angle: |
| E | Between 99.0 degrees and 100.0 degrees |
| S | Screw Material: |
| S | Steel comp 302 or steel comp 303 or steel comp 304 or steel comp 305 or steel comp 316 |
| S | Screw Material Specification: |
| 6 | 66 federal standard all material responses |
| S | Screw Surface Treatment: |
| C | Dxide |
| 1 | Thread Series Designator: |
| ι | Jnc |
| S | Shelf Life: |
| ١ | N/a |
| ι | Jnit Of Measure: |
| - | - |
| C | Demilitarization: |
| ٢ | No |
| F | Filg: |
| A | A500d0 |