NSN 5305-01-487-5189

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-487-5189 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.102 inches **Fastener Length:** 0.312 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.213 inches and 0.225 inches First Diameter From Head: Between 0.080 inches and 0.089 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.210 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.112 inches Thready Qty Per Inch (tpi): 40 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Externally Relieved Body Diameter Quantity:** 1 **Special Features:** Altered from nas514p440-5 Material: Steel comp 4130 or steel comp 4340 or steel comp 8740 **Material Specification:** Mil-s-6758 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, type ii, cl 3 federal specification single treatment response **Thread Series Designator:** Unjc

--

N/a

Shelf Life:

Unit Of Measure:

NSN 5305-01-487-5189

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6758 spec.