Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-487-5189

Thread Class:
За
Thread Direction:
Right-hand
Thread Length:
0.102 inches
Fastener Length:
0.312 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.213 inches and 0.225 inches
First Diameter From Head:
Between 0.080 inches and 0.089 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
0.210 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.112 inches
Thready Qty Per Inch (tpi):
40
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Externally Relieved Body Diameter Quantity:
1
Special Features:
Altered from nas514p440-5
Material:
Steel comp 4130 or steel comp 4340 or steel comp 8740
Material Specification:
Mil-s-6758 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military
specification 3rd material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416, type ii, cl 3 federal specification single treatment response
Thread Series Designator:
Unjc
Shelf Life:
N/a
Unit Of Measure:

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6758 spec.