NSN 5305-01-487-8230

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-487-8230 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.183 inches and 0.193 inches **Fastener Length:** 0.313 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.277 inches and 0.285 inches **Head Height:** Between 0.115 inches and 0.135 inches **Shoulder Diameter:** 0.155 inches first shoulder and 0.156 inches first shoulder **Shoulder Length:** 0.125 inches first shoulder and 0.127 inches first shoulder **Internal Drive Style:** Hexagon **End Application:** 5821-01-421-0805 **Thread Diameter:** 0.138 inches Width Across Flats: 0.094 inches Thready Qty Per Inch (tpi): **Shoulder Shape:** Round first shoulder Material: Steel comp 303 **Material Specification:** Astm a581 assn standard single material response or astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Mil-f-14072, type i military specification single treatment response **Thread Series Designator:**

Shelf Life: N/a

Unc

NSN 5305-01-487-8230

Shoulder Screw - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-f-14072 spec.