NSN 5305-01-490-5263

Panel Screw Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-490-5263

| Thread Class: |
|---|
| 3a |
| Thread Direction: |
| Right-hand |
| Fastener Length: |
| 0.813 inches |
| Head Style: |
| Hexagon |
| Head Height: |
| Between 0.185 inches and 0.190 inches |
| Width Between Flats: |
| Between 0.305 inches and 0.312 inches |
| Internal Drive Style: |
| Torx |
| End Application: |
| F-22 raptor |
| Material Accommodated Thickness: |
| 0.375 inches |
| Thread Diameter: |
| 0.190 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Product Name: |
| Screw |
| Material: |
| Iron alloy 660 |
| Surface Treatment: |
| |
| Passivate |
| Passivate Thread Series Designator: |
| |
| Thread Series Designator: |
| Thread Series Designator: Unjf |
| Thread Series Designator: Unjf Shelf Life: |
| Thread Series Designator: Unjf Shelf Life: N/a |
| Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: |
| Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: |
| Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization: |
| Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization: No |
| Thread Series Designator: Unjf Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: |