Externally Relieved Body Screw - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-01-491-0534

<b></b> .	
	aread Class:
2a	
	nread Direction:
	ght-hand
	aread Length:
	tween 0.365 inches and 0.375 inches
	stener Length:
	etween 1.470 inches and 1.530 inches
	ead Style:
	at chamfer
	ead Diameter:
	tween 0.615 inches and 0.635 inches
	ead Height:
	etween 0.240 inches and 0.260 inches
	rst Diameter From Head:
	etween 0.225 inches and 0.235 inches
	econd Diameter From Head:
	tween 0.214 inches and 0.230 inches
Di	stance From Largest Bearing Surface Of Head To End Of First Diameter:
	etween 0.865 inches and 0.885 inches
Di	stance From Largest Bearing Surface Of Head To End Of Second Diameter:
Be	etween 1.470 inches and 1.530 inches
Int	ternal Drive Style:
He	exagon
Th	read Diameter:
0.3	312 inches
Wi	idth Across Flats:
Be	tween 0.177 inches and 0.197 inches
Th	ready Qty Per Inch (tpi):
18	
Ex	ternally Relieved Body Diameter Quantity:
2	
Ма	aterial:
Sta	ainless steel
Ма	aterial Specification:
Qc	q-s-764; class 7; type a federal specification single material response
Su	Irface Treatment Specification:
Хх	b000 military specification single treatment response
Th	read Series Designator:
Ur	nc
Sh	nelf Life:
N/a	a

Externally Relieved Body Screw - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

spec.