NSN 5305-01-491-0534

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-491-0534 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.365 inches and 0.375 inches **Fastener Length:** Between 1.470 inches and 1.530 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.615 inches and 0.635 inches **Head Height:** Between 0.240 inches and 0.260 inches **First Diameter From Head:** Between 0.225 inches and 0.235 inches **Second Diameter From Head:** Between 0.214 inches and 0.230 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.865 inches and 0.885 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 1.470 inches and 1.530 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.312 inches Width Across Flats: Between 0.177 inches and 0.197 inches Thready Qty Per Inch (tpi): 18 **Externally Relieved Body Diameter Quantity:** Material: Stainless steel **Material Specification:** Qq-s-764; class 7; type a federal specification single material response **Surface Treatment Specification:** Xxb000 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

NSN 5305-01-491-0534

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:	
No	
Fiig:	
A003b0	

Mil-std (military Standard):

Unit Of Measure:

spec.