## NSN 5305-01-494-0033



Machine Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-494-0033 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 2.000 inches **Fastener Length:** 2.000 inches **Head Style:** Pan **Head Diameter:** Between 0.473 inches and 0.492 inches **Head Height:** Between 0.162 inches and 0.175 inches **Internal Drive Style:** Cross recess type iii **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 2540 pounds per square inch **Screw Material:** Steel comp 302 or steel comp 304 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 316 or steel comp 316 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 3 comp xm-7 **Screw Material Specification:** Qq-s-763 federal specification all material responses **Screw Surface Treatment:** Oxide **Screw Surface Treatment Specification:** Mil-c-13924, cl4 military specification single treatment response Color: Black **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:** 

Fiig: A500d0

No

**Demilitarization:** 

## NSN 5305-01-494-0033

Machine Screw - Page 2 of 2



Mil-std (military Standard):

Mil-c-13924 spec.