

View Online at <https://aerobasegroup.com/nsn/5305-01-494-0560>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.345 inches

**Fastener Length:**

0.657 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.372 inches and 0.381 inches

**Spline Minor Diameter:**

Between 0.1105 inches and 0.1125 inches

**Spline Major Diameter:**

Between 0.1540 inches and 0.1560 inches

**Grip Diameter:**

Between 0.188 inches and 0.189 inches

**Point Style:**

Flat

**Internal Drive Style:**

Torx

**End Application:**

F18 e/f

**Thread Diameter:**

0.190 inches

**Grip Length:**

0.313 inches

**Thready Qty Per Inch (tpi):**

32

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Criticality Code Justification:**

Agav

**Product Name:**

Bolt 100 degree tension head, gear drive recess-ph13-8mo (125 ksi shear), inconel 718 (125 ksi shear), 6al-4v titanium (95 ksi shear)

**Special Features:**

125 ksi ultimate shear strength; ivd aluminum coat

**Material:**

Stainless steel

**Material Specification:**

Inconel 718, per ams 5662 mfr ref 1st material response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0