NSN 5305-01-494-0615

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-494-0615

Thread Class:	
3a	
Thread Direction	:
Right-hand	
Thread Length:	
0.425 inches	
Fastener Length	
Between 1.092 in	ches and 1.122 inches
Head Style:	
Flat countersunk	
Head Diameter:	
Between 0.358 in	ches and 0.365 inches
Spline Minor Dia	meter:
Between 0.1105 i	nches and 0.1125 inches
Spline Major Dia	neter:
Between 0.1540 i	nches and 0.1560 inches
Grip Diameter:	
Between 0.2485 i	nches and 0.2495 inches
Internal Drive Sty	/le:
Torx	
End Application:	
F18 e/f	
Thread Diameter	
0.250 inches	
Grip Length:	
Between 0.672 in	ches and 0.692 inches
Thready Qty Per	Inch (tpi):
28	
Countersink Ang	le:
Between 99.0 deg	rees and 101.0 degrees
Product Name:	
Bolt, 100 degree	head, gear drive recess-ph13-8mo (125 ksi shear), inconel 718 (125 ksi shear), 6al-4v titanium (95 ksi shear)
Material:	
Nickel alloy 718	
Surface Treatme	nt:
Passivate	
Thread Series De	esignator:
Unjf	
Shelf Life:	
N/a	
Unit Of Measure:	

NSN 5305-01-494-0615

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

