Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-494-2079

Thread Class:
За
Thread Direction:
Right-hand
Thread Length:
1.000 inches
Fastener Length:
Between 1.460 inches and 1.500 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.365 inches and 0.375 inches
Head Height:
Between 0.244 inches and 0.250 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.250 inches
Width Across Flats:
Between 0.188 inches and 0.190 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
80000 pounds per square inch
Hardness Rating:
80.0 rockwell c
Minimum Yield Strength:
30000 pounds per square inch
Material:
Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-416, type 1, cl 2 federal specification single treatment response
Thread Series Designator:
Unrf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

NSN 5305-01-494-2079

Socket Head Cap Screw - Page 2 of 2

Fiig: A003b0

