

View Online at <https://aerobasegroup.com/nsn/5305-01-494-2265>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.344 inches

Fastener Length:

1.031 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.376 inches and 0.385 inches

Grip Diameter:

Between 0.1885 inches and 0.1894 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.190 inches

Grip Length:

0.687 inches

Width Across Flats:

Between 0.126 inches and 0.129 inches

Thready Qty Per Inch (tpi):

32

Countersink Angle:

100.0 degrees

Material:

Steel comp 4140 or steel comp 4340 or steel comp 8740

Material Specification:

Ams6382 assn standard 1st material response or mil-s-5626 military specification 1st material response or ams648 assn standard 2nd material response or ams6414 assn standard 2nd material response or mil-s-8844 military specification 2nd material response or ams6415 assn standard 2nd material response or ams6322 assn standard 3rd material response or mil-s-6049 assn standard 3rd material response

Surface Treatment:

Cadmium grip

Surface Treatment Specification:

Qq-p-416, ty ii federal specification single treatment response grip

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.