NSN 5305-01-494-2265

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-494-2265

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.344 inches
Fastener Length:
1.031 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.376 inches and 0.385 inches
Grip Diameter:
Between 0.1885 inches and 0.1894 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.190 inches
Grip Length:
0.687 inches
Width Across Flats:
Between 0.126 inches and 0.129 inches
Thready Qty Per Inch (tpi):
32
Countersink Angle:
100.0 degrees
Material:
Steel comp 4140 or steel comp 4340 or steel comp 8740
Material Specification:
Ams6382 assn standard 1st material response or mil-s-5626 military specification 1st material response or ams648 assn standard 2nd
material response or ams6414 assn standard 2nd material response or mil-s-8844 military specification 2nd material response or ams6415
assn standard 2nd material response or ams6322 assn standard 3rd material response or mil-s-6049 assn standard 3rd material response
Surface Treatment:
Cadmium grip
Surface Treatment Specification:
Qq-p-416, ty ii federal specification single treatment response grip
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5305-01-494-2265

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.