

View Online at <https://aerobasegroup.com/nsn/5305-01-494-3346>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.578 inches

**Fastener Length:**

Between 1.688 inches and 1.718 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.7409 inches and 0.7604 inches

**Spline Minor Diameter:**

Between 0.3735 inches and 0.3745 inches

**Spline Major Diameter:**

Between 1.115 inches and 1.135 inches

**Grip Diameter:**

Between 0.3735 inches and 0.3745 inches

**Internal Drive Style:**

Torx

**End Application:**

F18 e/f

**Thread Diameter:**

0.3750 inches

**Grip Length:**

Between 1.115 inches and 1.135 inches

**Thready Qty Per Inch (tpi):**

24

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Product Name:**

Bolt, 100 degree tension head, gear drive recess-ph13-8mo (125 ksi shear), inconel 718 (125 ksi shear), 6al-4v titanium (95 ksi shear)

**Material:**

Nickel alloy 718

**Material Specification:**

Ams 5662 assn standard single material response

**Surface Treatment:**

Aluminum

**Surface Treatment Specification:**

Mil-c-83488 military specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-83488 spec.