

View Online at <https://aerobasegroup.com/nsn/5305-01-494-5605>

Thread Direction:

Right-hand

Thread Length:

Between 22.6 millimeters and 25.4 millimeters

Fastener Length:

Between 39.6 millimeters and 40.4 millimeters

Head Style:

Flat chamfer

Head Diameter:

Between 9.7 millimeters and 10.0 millimeters

Head Height:

Between 5.8 millimeters and 6.0 millimeters

Internal Drive Style:

Hexagon

End Application:

Interim armored vehicle (iav), contractor logistics support (cls)

Thread Diameter:

6.0 millimeters

Width Across Flats:

Between 5.0 millimeters and 5.1 millimeters

Min. Tensile Strength (psi):

1220 megapascals

Hardness Rating:

38.0 rockwell c and 44.0 rockwell c

Minimum Yield Strength:

1100 megapascals

Thread Pitch In Millimeters:

1.0

External Thread Tolerance Class:

4g6g

Material:

Steel property class 12.9

Surface Treatment:

Zinc and chromate

Surface Treatment Specification:

Astm b633, type 2, cl 3 assn standard single treatment response

Thread Series Designator:

M

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0