NSN 5305-01-494-7020

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-494-7020

view Offilite at https://aerobasegroup.com/hist//0500-01-404-7020
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.403 inches
Fastener Length:
Between 0.575 inches and 0.605 inches
Head Style:
Flat countersunk
Head Diameter:
0.464 inches
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Point Style:
Flat
Internal Drive Style:
Torque-set ribbed
Thread Diameter:
0.2500 inches
Grip Length:
Between 0.177 inches and 0.197 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
5790 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Material:
Iron alloy 660
Material Specification:
Ams5731 assn standard single material response or ams5732 assn standard single material response or ams5737 assn standard single
material response or ams5853 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1580 professional/industrial association standard

N/a

Shelf Life:

NSN 5305-01-494-7020

Close Tolerance Screw - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A003b0