

View Online at <https://aerobasegroup.com/nsn/5305-01-494-7022>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.501 inches

Fastener Length:

Between 0.986 inches and 1.016 inches

Head Style:

Flat countersunk

Head Diameter:

0.578 inches

Grip Diameter:

Between 0.3110 inches and 0.3120 inches

Point Style:

Flat

Internal Drive Style:

Torque-set ribbed

Thread Diameter:

0.3125 inches

Grip Length:

Between 0.490 inches and 0.510 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

9260 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Iron alloy 660

Material Specification:

Ams5731 assn standard single material response or ams5732 assn standard single material response or ams5737 assn standard single material response or ams5853 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

8205-nas1580 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0