Socket Head Cap Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-494-7336

| Thread Direction: |
|---|
| Right-hand |
| Thread Length: |
| 12.0 millimeters |
| Fastener Length: |
| 12.0 millimeters |
| Head Style: |
| Flat countersunk |
| Head Diameter: |
| Between 9.75 millimeters and 11.20 millimeters |
| Internal Drive Style: |
| Hexagon |
| End Application: |
| Interim armored vehicle (iav), contractor logistics support (cls) |
| Thread Diameter: |
| 5.0 millimeters |
| Width Across Flats: |
| 3.0 millimeters |
| Thread Pitch In Millimeters: |
| 0.8 |
| External Thread Tolerance Class: |
| 4h6h |
| Countersink Angle: |
| Between 90.0 degrees and 92.0 degrees |
| Material: |
| Steel |
| Surface Treatment: |
| Zinc and chromate |
| Surface Treatment Specification: |
| Astm b633, type 2 federal standard single treatment response |
| Thread Series Designator: |
| Μ |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A003b0 |
| |
| |