NSN 5305-01-494-8236

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-494-8236 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.630 inches and 0.697 inches **Fastener Length:** Between 1.745 inches and 1.822 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.881 inches and 0.888 inches **Head Height:** Between 0.130 inches and 0.133 inches **Grip Diameter:** Between 0.3115 inches and 0.3120 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.438 inches **Grip Length:** Between 1.115 inches and 1.135 inches Thready Qty Per Inch (tpi): 20 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 32.0 microinches threads **Product Name:** Navy special project Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

NSN 5305-01-494-8236

Close Tolerance Screw - Page 2 of 2



	• •						
ın	18	Of	ΝЛ	ດລ	CI.	ır	ο.

--

Demilitarization:

No

Fiig:

A003b0