NSN 5305-01-494-8910

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-494-8910 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.625 inches and 0.672 inches **Fastener Length:** Between 1.2970 inches and 1.4320 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.7556 inches and 0.7604 inches **Head Height:** Between 0.1147 inches and 0.1167 inches **Grip Diameter:** Between 0.3740 inches and 0.3745 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.3750 inches **Grip Length:** Between 0.740 inches and 0.760 inches Thready Qty Per Inch (tpi): 24 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Special Features:** Furnished with one oring Material: Steel comp xm-13 **Material Specification:** Ams5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a
Unit Of Measure:

NSN 5305-01-494-8910

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0