NSN 5305-01-494-9015

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-494-9015 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.630 inches and 0.697 inches **Fastener Length:** Between 1.807 inches and 1.894 inches **Head Style:** Flat countersunk undercut **Head Diameter:** Between 0.881 inches and 0.888 inches **Head Height:** Between 0.130 inches and 0.133 inches **Grip Diameter:** Between 0.4365 inches and 0.4370 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.438 inches **Grip Length:** Between 1.1775 inches and 1.1975 inches Thready Qty Per Inch (tpi): 20 **Countersink Angle:** 99.0 degrees **Surface Finish:** 32.0 microinches threads Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a **Unit Of Measure:**

NSN 5305-01-494-9015

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0