NSN 5305-01-494-9087

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-494-9087

| Thread Class: |
|---|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.625 inches and 0.672 inches |
| Fastener Length: |
| Between 1.2970 inches and 1.6195 inches |
| |
| Head Style: Flat countersunk undercut |
| Head Diameter: |
| Between 0.7556 inches and 0.7604 inches |
| Head Height: |
| Between 0.1147 inches and 0.1167 inches |
| Grip Diameter: |
| Between 0.3740 inches and 0.3745 inches |
| |
| Internal Drive Style: |
| High-torque Thread Diameter: |
| 0.3750 inches |
| Grip Length: |
| Between 0.9275 inches and 0.9475 inches |
| |
| Thready Qty Per Inch (tpi): 24 |
| |
| Countersink Angle: Between 99.0 degrees and 101.0 degrees |
| Product Name: |
| Navy special project |
| |
| Special Features: |
| Furnished with one oring Material: |
| |
| Steel comp xm-13 |
| Material Specification: |
| Ams5629 assn standard single material response Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator: |
| Unjf Shelf Life: |
| |
| N/a |

NSN 5305-01-494-9087

Close Tolerance Screw - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

