

View Online at <https://aerobasegroup.com/nsn/5305-01-494-9271>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.625 inches and 0.672 inches

**Fastener Length:**

Between 1.2970 inches and 1.7445 inches

**Head Style:**

Flat countersunk undercut

**Head Diameter:**

Between 0.7556 inches and 0.7604 inches

**Head Height:**

Between 0.1147 inches and 0.1167 inches

**Grip Diameter:**

Between 0.3740 inches and 0.3745 inches

**Internal Drive Style:**

High-torque

**Thread Diameter:**

0.3750 inches

**Grip Length:**

Between 1.0525 inches and 1.0725 inches

**Thready Qty Per Inch (tpi):**

24

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Special Features:**

Furnished with one oring

**Material:**

Steel comp xm-13

**Material Specification:**

Ams5629 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0