## NSN 5305-01-495-0587

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-495-0587 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.288 inches **Fastener Length:** Between 0.6255 inches and 0.6755 inches **Head Style:** Fillister countersunk **Head Diameter:** 0.339 inches **Head Height:** 0.015 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches Point Style: Flat **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.3025 inches and 0.3225 inches Thready Qty Per Inch (tpi): 32 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp 4140 or steel comp 4340 or steel comp 8740 **Material Specification:** Mil-s-5626 military specification 1st material response or ams6415 assn standard 2nd material response or mil-s-6049 military specification 3rd material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, ty2cl2 federal specification single treatment response **Thread Series Designator:** Unjf

N/a

Shelf Life:

**Unit Of Measure:** 

## NSN 5305-01-495-0587

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.