

View Online at <https://aerobasegroup.com/nsn/5305-01-495-0587>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.288 inches

Fastener Length:

Between 0.6255 inches and 0.6755 inches

Head Style:

Fillister countersunk

Head Diameter:

0.339 inches

Head Height:

0.015 inches

Grip Diameter:

Between 0.1885 inches and 0.1895 inches

Point Style:

Flat

Internal Drive Style:

Offset cruciform (torque set)

Thread Diameter:

0.190 inches

Grip Length:

Between 0.3025 inches and 0.3225 inches

Thready Qty Per Inch (tpi):

32

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Steel comp 4140 or steel comp 4340 or steel comp 8740

Material Specification:

Mil-s-5626 military specification 1st material response or ams6415 assn standard 2nd material response or mil-s-6049 military specification 3rd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, ty2cl2 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.