NSN 5305-01-495-9256

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-495-9256

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.420 inches and 0.430 inches
Fastener Length:
Between 0.910 inches and 0.940 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.497 inches and 0.506 inches
Spline Major Diameter:
Between 0.154 inches and 0.156 inches
Grip Diameter:
0.249 inches
Point Diameter:
0.425 inches
Point Style:
Flat
Internal Drive Style:
Torx
Thread Diameter:
0.250 inches
Grip Length:
Between 0.490 inches and 0.510 inches
Thready Qty Per Inch (tpi):
28
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Product Name:
Bolt, 100 degree tension "head, gear drive recess
Special Features:
125 ksi shear strength
Material:
Nickel alloy 718
Material Specification:
Ams 5662 assn standard single material response
Surface Treatment:
Passivate
Thread Series Designator:
Unjf
origi

NSN 5305-01-495-9256

Close Tolerance Screw - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

