## NSN 5305-01-495-9257

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-495-9257 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.345 inches **Fastener Length:** Between 0.5175 inches and 0.5475 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.265 inches and 0.272 inches **Spline Minor Diameter:** Between 0.1105 inches and 0.1125 inches **Spline Major Diameter:** Between 0.1540 inches and 0.1560 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** Torx **End Application:** F18 e/f **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.1775 inches and 0.1975 inches Thready Qty Per Inch (tpi): **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Nickel alloy 718 **Material Specification:** Ams 5662 assn standard single material response **Surface Treatment: Passivate Thread Series Designator:** Unjf Shelf Life: N/a

Unit Of Measure:

## NSN 5305-01-495-9257

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0