

View Online at <https://aerobasegroup.com/nsn/5305-01-496-1417>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.375 inches

Fastener Length:

Between 2.485 inches and 2.515 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.358 inches and 0.365 inches

Hole Diameter:

Between 0.076 inches and 0.081 inches

Spline Minor Diameter:

Between 0.1105 inches and 0.1125 inches

Spline Major Diameter:

Between 0.1540 inches and 0.1560 inches

Grip Diameter:

Between 0.2485 inches and 0.2495 inches

Internal Drive Style:

Torx

End Application:

F18 e/f

Thread Diameter:

0.250 inches

Grip Length:

Between 2.115 inches and 2.135 inches

Hole Quantity:

1

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

28

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Product Name:

Bolt, 100 degree reduced head, gear drive recess-special thread length inconcel 718 (125 ksi shear)

Material:

Nickel alloy 718

Material Specification:

Bps-f-69 mfr ref single material response

Surface Treatment:

Passivate

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0