

View Online at <https://aerobasegroup.com/nsn/5305-01-496-1429>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.345 inches

**Fastener Length:**

Between 0.580 inches and 0.610 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.265 inches and 0.272 inches

**Spline Minor Diameter:**

Between 0.1105 inches and 0.1125 inches

**Spline Major Diameter:**

Between 0.1540 inches and 0.1560 inches

**Grip Diameter:**

Between 0.1885 inches and 0.1895 inches

**Internal Drive Style:**

Torx

**End Application:**

F18 e.F

**Thread Diameter:**

0.190 inches

**Grip Length:**

Between 0.240 inches and 0.250 inches

**Thready Qty Per Inch (tpi):**

32

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Product Name:**

Bolt, 100 degrees reduced head, gear drive recess-ph13-8mo (125 ksi shear), inconel 718 (125 ksi shear), 6al-4v titanium (95 ksi shear)

**Material:**

Nickel alloy 718

**Material Specification:**

Ams 5662 assn standard single material response

**Surface Treatment:**

Passivate

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0