NSN 5305-01-496-4889

Externally Relieved Body Screw - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5305-01-496-4889 |
|---|
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.340 inches |
| Fastener Length: |
| 1.100 inches |
| Head Style: |
| Flat chamfer |
| Head Diameter: |
| 0.308 inches |
| Head Height: |
| 0.190 inches |
| Internal Drive Style: |
| Hexagon |
| End Application: |
| Disp and conl s |
| Thread Diameter: |
| 0.190 inches |
| Width Across Flats: |
| Between 0.1562 inches and 0.1587 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Externally Relieved Body Diameter Quantity: |
| 1 |
| Material: |
| Stainless steel |
| Material Specification: |
| Astm a276; cond a assn standard single material response |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator: |
| Unf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 5305-01-496-4889

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0