

View Online at <https://aerobasegroup.com/nsn/5305-01-497-0735>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.656 inches

**Fastener Length:**

Between 2.202 inches and 2.249 inches

**Head Style:**

Flat countersunk undercut

**Head Diameter:**

Between 0.881 inches and 0.888 inches

**Head Height:**

Between 0.130 inches and 0.133 inches

**Grip Diameter:**

Between 0.436 inches and 0.437 inches

**Internal Drive Style:**

High-torque

**End Application:**

Cbil for c/d/

**Thread Diameter:**

0.438 inches

**Grip Length:**

1.562 inches

**Thready Qty Per Inch (tpi):**

20

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Surface Finish:**

32.0 microinches threads

**Product Name:**

Navy special project

**Material:**

Steel comp xm-13

**Material Specification:**

Ams5629, comp xm-13 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0