NSN 5305-01-497-0735

Thread Class:

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-497-0735

| 3a | | | | | |
|--|--|--|--|--|--|
| Thread Direction: | | | | | |
| Right-hand | | | | | |
| Thread Length: | | | | | |
| 0.656 inches | | | | | |
| Fastener Length: | | | | | |
| Between 2.202 inches and 2.249 inches | | | | | |
| Head Style: | | | | | |
| Flat countersunk undercut | | | | | |
| Head Diameter: | | | | | |
| Between 0.881 inches and 0.888 inches | | | | | |
| Head Height: | | | | | |
| Between 0.130 inches and 0.133 inches | | | | | |
| Grip Diameter: | | | | | |
| Between 0.436 inches and 0.437 inches | | | | | |
| Internal Drive Style: | | | | | |
| High-torque | | | | | |
| End Application: | | | | | |
| Cbil for c/d/ | | | | | |
| Thread Diameter: | | | | | |
| 0.438 inches | | | | | |
| Grip Length: | | | | | |
| 1.562 inches | | | | | |
| Thready Qty Per Inch (tpi): | | | | | |
| 20 | | | | | |
| Countersink Angle: | | | | | |
| Between 99.0 degrees and 101.0 degrees | | | | | |
| Surface Finish: | | | | | |
| 32.0 microinches threads | | | | | |
| Product Name: | | | | | |
| Navy special project | | | | | |
| Material: | | | | | |
| Steel comp xm-13 | | | | | |
| Material Specification: | | | | | |
| Ams5629, comp xm-13 assn standard single material response | | | | | |
| Surface Treatment: | | | | | |
| Passivate | | | | | |
| Surface Treatment Specification: | | | | | |
| Qq-p-35 federal specification single treatment response | | | | | |
| Thread Series Designator: | | | | | |
| Unjf | | | | | |

NSN 5305-01-497-0735

Close Tolerance Screw - Page 2 of 2



| | | fe | |
|--|--|----|--|
| | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0