

View Online at <https://aerobasegroup.com/nsn/5305-01-497-6140>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.4688 inches and 0.5312 inches

Fastener Length:

Between 1.7188 inches and 1.7812 inches

Head Style:

Hexagon

Head Height:

Between 0.2188 inches and 0.2812 inches

Width Between Flats:

Between 0.5313 inches and 0.5937 inches

Shoulder Length:

0.2188 inches first shoulder and 0.2812 inches first shoulder

Shoulder Width Across Flats:

0.5313 inches first shoulder and 0.5937 inches first shoulder

Internal Drive Style:

Hexagon

End Application:

Interim armored vehicl (iav), contractor logistic support(cls)

Thread Diameter:

0.312 inches

Width Across Flats:

0.188 inches

Thready Qty Per Inch (tpi):

18

Shoulder Shape:

Hexagonal first shoulder

Material:

Steel comp 303 or steel comp 304 or steel comp xm-7

Surface Treatment:

Passivate

Surface Treatment Specification:

Sa3-qq-+35 assn standard 1st treatment response

Thread Series Designator:

Unc

Specification Data:

80205-nas51576 professional/industrial association standard

Specification Or Standard:

35 form

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0