

View Online at <https://aerobasegroup.com/nsn/5305-01-497-9724>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.338 inches

Fastener Length:

Between 1.573 inches and 1.603 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.339 inches and 0.381 inches

Grip Diameter:

Between 0.219 inches and 0.220 inches

Internal Drive Style:

High-torque

Thread Diameter:

0.190 inches

Grip Length:

1.250 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Steel comp 4140 or steel comp 4340 or steel comp e4340

Material Specification:

Mil-s-5626 military specification 1st material response or ams6415 assn standard 2nd material response or mil-s-5000 military specification 3rd material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, ty ii, cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas1790 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.