## NSN 5305-01-498-4597

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-498-4597 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.425 inches **Fastener Length:** Between 1.348 inches and 1.378 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.449 inches and 0.507 inches **Grip Diameter:** Between 0.248 inches and 0.249 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.928 inches and 0.948 inches Thready Qty Per Inch (tpi): 28 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp 4140 or steel comp e4340 **Material Specification:** Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Qq-p-416, tyii, cl2 federal specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No Fiig:

A003b0

## NSN 5305-01-498-4597

Close Tolerance Screw - Page 2 of 2



Mil-std (military Standard):

Mil-s-5626 spec.