NSN 5305-01-499-6023

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-499-6023 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.360 inches **Fastener Length:** 1.125 inches **Head Style:** Hexagon **Head Height:** Between 0.226 inches and 0.243 inches Width Between Flats: Between 0.551 inches and 0.562 inches First Diameter From Head: 0.290 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.765 inches **Internal Drive Style:** W/o internal drive **End Application:** 2350-01-420-4716 **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 16 **Externally Relieved Body Diameter Quantity:** Material: Steel comp 304 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 316l or steel comp 384 or steel comp xm-7 **Material Specification:** Astm f593 assn standard single material response **Surface Treatment: Passivate Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

Demilitarization:

No

NSN 5305-01-499-6023

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0