Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-499-7919



Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 0.497 inches and 0.529 inches Fastener Length: Between 0.609 inches and 0.641 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.311 inches and 0.359 inches Locking Feature: Strip threads or patch threads **Internal Drive Style:** Hexagon **Thread Diameter:** 0.164 inches Width Across Flats: Between 0.0937 inches and 0.0947 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 43.0 rockwell c Minimum Yield Strength: 130000 pounds per square inch **Countersink Angle:** 82.0 degrees Material: Steel Surface Treatment: Cadmium and chromate Surface Treatment Specification: Qq-p-416, type 2, cl 3 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a Unit Of Measure: ---

NSN 5305-01-499-7919

Socket Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

