NSN 5305-01-500-1915

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-500-1915

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.276 inches
Fastener Length:
Between 0.886 inches and 0.916 inches
Head Style:
Flat fillister
Head Diameter:
Between 0.265 inches and 0.270 inches
Head Height:
Between 0.088 inches and 0.102 inches
Grip Diameter:
Between 0.1625 inches and 0.1635 inches
Internal Drive Style:
Offset cruciform (torque set)
End Application:
F-22 acft
Thread Diameter:
0.164 inches
Grip Length:
Between 0.615 inches and 0.635 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Product Name:
Screw, machine-flat fillister head, close tol, short thd
Material:
Iron alloy 660
Material Specification:
Ams5737 assn standard single material response
Thread Series Designator:
Unjc
Specification Data:
80205-nas1122 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

NSN 5305-01-500-1915

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

