## NSN 5305-01-500-6403

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-500-6403 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.735 inches **Fastener Length:** Between 2.4700 inches and 2.5000 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.6230 inches and 0.6335 inches **Spline Minor Diameter:** Between 0.1570 inches and 0.1600 inches **Spline Major Diameter:** Between 0.2195 inches and 0.2225 inches **Grip Diameter:** Between 0.3110 inches and 0.3120 inches **Internal Drive Style:** Torx **End Application:** F18 e/f **Thread Diameter:** 0.500 inches **Grip Length:** Between 0.9275 inches and 0.9475 inches Thready Qty Per Inch (tpi): 20 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Criticality Code Justification:** Agav **Product Name:** Bolt, 100 degree tension head, gear drive recess-ph13-8mo (125 ksi shear), inconel 718 (125 ksi shear), 6al-4v titanium (95 ksi shear) Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response

**Passivate** 

**Surface Treatment:** 

**Thread Series Designator:** 

Unjf

## NSN 5305-01-500-6403

Close Tolerance Screw - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0