

NSN 5305-01-500-8179 Close Tolerance Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-500-8179 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.345 inches **Fastener Length:** Between 0.6425 inches and 0.6725 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.3729 inches and 0.3813 inches **Spline Minor Diameter:** Between 0.1105 inches and 0.1125 inches **Spline Major Diameter:** Between 0.1540 inches and 0.1560 inches **Grip Diameter:** Between 0.1890 inches and 0.1895 inches **Point Style:** Flat **Internal Drive Style:** Torx **End Application:** F18 e/f **Thread Diameter:** 0.190 inches **Grip Length:**

Between 0.3025 inches and 0.3225 inches

Thready Qty Per Inch (tpi):

32

Countersink Angle:

Between 99.0 degrees and 101.00 degrees

Product Name:

Bolt, 100 degree tension head, gear drive recess

Special Features:

125 ksi shear strength

Material:

Nickel alloy 718

Material Specification:

Aams 5662 assn standard single material response

Surface Treatment:

Passivate

NSN 5305-01-500-8179

Close Tolerance Screw - Page 2 of 2



Thread Series Designator:
Unjf
Shelf Life:
N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0