Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-501-1474

| hread Direction: |
|---|
| light-hand |
| 'hread Length: |
| 4.0 millimeters |
| astener Length: |
| 4.0 millimeters |
| lead Style: |
| Pan no. 2 |
| lead Diameter: |
| Setween 6.8 millimeters and 7.0 millimeters |
| lead Height: |
| Between 3.9 millimeters and 4.0 millimeters |
| nternal Drive Style: |
| lexagon |
| Ind Application: |
| nterim armored vehicle (iav), contractor logistics support (cls) |
| hread Diameter: |
| .0 millimeters |
| Vidth Across Flats: |
| .0 millimeters |
| hread Pitch In Millimeters: |
| .7 |
| External Thread Tolerance Class: |
| g6g |
| Product Name: |
| letric socket head cap screw |
| pecial Features: |
| laterial is alloy steel per 12.9 property class |
| faterial: |
| steel property class 12.9 |
| Surface Treatment: |
| Passivate |
| Surface Treatment Specification: |
| stm a 380 assn standard single treatment response |
| Supplementary Features: |
| his screw has no special features; nsn 530501501147 has the same dimensions but has special features (drilled head and self-locking |
| hread Series Designator: |
| Λ |
| Shelf Life: |
| I/a |
| Init Of Measure: |
| |

NSN 5305-01-501-1474

Socket Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

