

View Online at <https://aerobasegroup.com/nsn/5305-01-501-7161>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.188 inches

**Fastener Length:**

Between 0.157 inches and 0.188 inches

**Head Style:**

Flat fillister

**Head Diameter:**

Between 0.306 inches and 0.313 inches

**Head Height:**

Between 0.103 inches and 0.118 inches

**Internal Drive Style:**

Cross recess type 1

**End Application:**

Fuselage sect

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Screw Material:**

Steel comp 4140 or steel comp 4340 or steel comp 8740

**Locking Feature Material:**

Plastic polyamide

**Screw Material Specification:**

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response

**Screw Surface Treatment:**

Cadmium and chromate

**Screw Surface Treatment Specification:**

Qq-p-416, type 2, class 2 federal specification all treatment responses

**Special Features:**

Item is self locking

**Thread Series Designator:**

Unjf

**Specification Data:**

80205-nas1191 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A500d0

**Mil-std (military Standard):**

Mil-s-5626 spec.