NSN 5305-01-501-8756

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-501-8756 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.335 inches and 0.355 inches **Fastener Length:** Between 1.455 inches and 1.485 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.265 inches and 0.272 inches **Spline Minor Diameter:** Between 0.1105 inches and 0.1125 inches **Spline Major Diameter:** Between 0.1540 inches and 0.1560 inches **Grip Diameter:** Between 0.1890 inches and 0.1895 inches **Internal Drive Style:** Torx **End Application:** F/a-18e/f forward fuselage **Thread Diameter:** 0.1900 inches **Grip Length:** Between 1.115 inches and 1.135 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 2200 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Nickel alloy **Material Specification:** Ams 5662 assn standard single material response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-01-501-8756

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0