## NSN 5305-01-502-6870

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-502-6870 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.360 inches and 0.375 inches **Fastener Length:** 2.000 inches **Head Style:** Knurled no. 5 **Head Diameter:** Between 0.240 inches and 0.260 inches **Head Height:** Between 0.438 inches and 0.453 inches **First Diameter From Head:** Between 0.125 inches and 0.135 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 1.625 inches **Point Style:** Cone **Internal Drive Style:** Slot **End Application:** 1430-01-378-6963 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity: Point Chamfer Angle:** Between 77.0 degrees and 87.0 degrees **Product Name:** Captive panel screw type 101 Color: Black Material: Stainless steel **Surface Treatment:** Oxide **Thread Series Designator:** 

Unc

## NSN 5305-01-502-6870

Externally Relieved Body Screw - Page 2 of 2



SI	nel	lf I	l if	ρ.
Ο.		•		v.

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0