NSN 5305-01-503-0933

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-503-0933 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.501 inches **Fastener Length:** Between 1.674 inches and 1.704 inches **Head Style:** Flat countersunk **Head Diameter:** 0.633 inches **Grip Diameter:** Between 0.311 inches and 0.312 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.312 inches **Grip Length:** 1.188 inches Thready Qty Per Inch (tpi): 24 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Steel comp 4140 or steel comp 4340 or steel comp 8740 **Material Specification:** Mil-s-5626 military specification 1st material response or ams6415 assn standard 2nd material response or mil-s-6049 military specification 3rd material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** 11-p-416, ty ii, cl 2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1580 professional/industrial association standard Shelf Life: N/a

Demilitarization:

Unit Of Measure:

No

NSN 5305-01-503-0933

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.