NSN 5305-01-504-3736

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-504-3736

view offilite at https://aerobasegroup.com/har//5505-01-504-5750
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.276 inches
Fastener Length:
Between 1.886 inches and 1.916 inches
Head Style:
Pan
Head Diameter:
Between 0.256 inches and 0.270 inches
Head Height:
Between 0.087 inches and 0.097 inches
Grip Diameter:
Between 0.1365 inches and 0.1375 inches
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.138 inches
Grip Length:
1.625 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Material:
Steel comp 4140 or steel comp e4340 or steel comp 8740
Material Specification:
Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military
specification 3rd material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 ty2 cl2 federal specification single treatment response
Thread Series Designator:
Unjc
Specification Data:
80205-nas1131 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5305-01-504-3736

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.