## NSN 5305-01-505-4004

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-505-4004

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.4357 inches
Fastener Length:
Between 0.860 inches and 0.890 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.265 inches and 0.272 inches
Spline Minor Diameter:
Between 0.1105 inches and 0.1125 inches
Spline Major Diameter:
Between 0.1540 inches and 0.1560 inches
Grip Diameter:
Between 0.1885 inches and 0.1895 inches
Internal Drive Style:
Torx
End Application:
F18 e/f
Thread Diameter:
0.190 inches
Grip Length:
Between 0.428 inches and 0.448 inches
Thready Qty Per Inch (tpi):
32
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Product Name:
Bolt, 100 degree reduced head, gear drive recess-special thread length inconcel 718 (125 ksi shear)
Material:
Nickel alloy 718
Material Specification:
Bps-f-69 mfr ref single material response
Surface Treatment:
Passivate
Thread Series Designator:
Unjf
Shelf Life:
N/a

## NSN 5305-01-505-4004

Close Tolerance Screw - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

