NSN 5305-01-505-4050

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-505-4050 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.250 inches **Fastener Length:** Between 0.485 inches and 0.515 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.358 inches and 0.365 inches **Spline Minor Diameter:** Between 0.1105 inches and 0.1125 inches **Spline Major Diameter:** Between 0.1540 inches and 0.1560 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Internal Drive Style:** Torx **End Application:** F18 e/f **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.240 inches and 0.260 inches Thready Qty Per Inch (tpi): **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Product Name:** Bolt, 100 degree reduced head, gear drive recess-special thread length inconcel 718 (125 ksi shear) Material: Nickel alloy 718 **Material Specification:** Bps-f-69 mfr ref single material response **Surface Treatment: Passivate Thread Series Designator:**

N/a

Unjf

Shelf Life:

NSN 5305-01-505-4050

Close Tolerance Screw - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A003b0